

TOP SANDER

TOPSANDER is a small and effective sanding machine for mouldings. The machine is suitable for long wooden components, door framing, window-components, The sanding unit is powered by electric motor with frequency inverter for precise adjustment of the sanding speed to assure perfect sanding result.



Mounted with BSA sandingpaper – the most versatile brush sanding system in the world. Grades from P60 - P600. Supplied in cut 3-5-10-20 or no cut.

3 different heights rounds up the system (30, 46 og 61mm).

Indicator for each track.

TOP SANDER 200 are supplied with 200mm sanding wheel – Ø180mm core.

The machine is build in a solid steel construction og is mounted with aut. Belt conveyor.

- Belt length 1200mm
- Integrated controlpanel
- Adjustable sanding pressure 5-80mm
- Dust extraction 1 x Ø90mm
- Control left side

The compact design only requires 1250 x 500 x 1400mm.

Supplied with Quick Change system



1301-TOP-200

2 x Brushmotor
0,37Kw, 380V

180mm brush sanding wheels

Working width 200mm

Sanding cloth 46mm, P180, cut 5+10mm

Frequency regulation of sanding speed 50-500rpm

Feeding motor 1 x 0,55kW
Frequency inverter 5-15m/min



BSA KONCEPT

Separated brush & sanding strip



Stærmosevej 190
DK – 5690 Tommerup

Tel. 0045 70 20 09 39



Garnisonsvägen 30
S – 281 35 Hässleholm

bolltec@bolltec.com



www.bolltec.com